
LAVA® BASIC - DM - The ideal solution for heating from the ceiling.



USE

The already proven LAVA® BASIC - DM is suitable for heating from the ceiling, for example, for discreet heating in living areas, offices, bathrooms, schools, containers, etc. LAVA® BASIC - DM is a 22 mm flat infrared radiant heater characterised by its uniform infrared heat and aesthetics.

Mounted on the ceiling or in suspended ceilings, the heaters are ideally suited for full heating or zone heating. When installed in the ceiling, the heat radiator is fully integrated into the ceiling. Ceiling mounting allows optimal use of the area and damage as a result of jolting the heater is avoided. Available in the colour White RAL 9016 and in 5 capacities.



Suspended ceilings

TECHNICAL DATA

 $(\in$

> Voltage: 230 V

Output: 350, 500, 750, 1000, 1500 Watt

Surface temperature: max. 120 °C
Surface: Structured surface, white RAL 9016

Device/Installation depth: 22/52 mmProtection rating: IP 21

> Cable: 1 m, 3 x 1.5 mm² without plug

> Factory warranty: 5 years

BENEFITS OF THIS PRODUCT

- + Lightweight design Easy ceiling mounting
- + Large infrared emitting surface
- + Maintenance free and magnetic field free
- + High proportion of radiation
- + 350, 750 and 1500 W suitable for suspended ceilings
- + Also suitable for wall mounting

SELECTION GUIDE

The selection of the output depends on the heat demand of the room (height: 2.5 m) and the heating application.

The following is a guide:

20-45 W/m² Low energy and passive house
50-70 W/m² Well insulated housing
75-95 W/m² Moderately insulated housing
100-120 W/m² Poorly insulated housing

LAVA® BASIC - DM, infrared heating with no control

RG: 018 | DT: 1 week

Туре	Order no.	Control system	Output (W)	Dimensions (mm)		Weight
				Length	Height	(kg)
LAVA-BASIC-350DM	39692	none	350	620	620	7.5
LAVA-BASIC-500DM	39622	none	500	900	620	12
LAVA-BASIC-750DM	39623	none	750	1245	620	16
LAVA-BASIC-1000DM	39624	none	1000	1600	620	21
LAVA-BASIC-1500DM	39723	none	1500	1245	1245	32

Accessories

RG: 007 | DT: ex stock

Model	Order no.	Description
ET-71	38692	Switch mounted thermostat, 10-45 °C, 16 A, colour: white; remote sensor included
eTOUCH-mini-black	39299	Switch mounted thermostat with black touchpad, 16 A, 5-40 °C, 2 frames in white and black included
eTOUCH-mini-white	39300	Switch mounted thermostat with white touchpad, 16 A. 5-40 °C, 2 frames in white and black included
ET-11A	35891	Radio room thermostat, LCD display
ET-12A	35890	Radio room thermostat, LCD display with clock and week program
ET-111A	36758	Radio receiver with 16 A relay in wall-mounted housing