

LAVA® Plug & Play control system

The control you've always wanted.

Modern, precise control is the key to saving operating costs and avoiding wasting valuable energy. The various types of the LAVA® design infrared heaters in combination with an appropriate thermostat, provides the ideal solution for every individual need.

Thanks to the new Plug & Play connection system, you can tailor your LAVA® Design infrared heaters to your individual needs at any time. For instance, you can upgrade the standard model at a later stage with a thermostat or a radio receiver.



LAVA®-F - Radio receiver with 16 A relay in wall-mounted housing



USE

The LAVA®-F radio receiver, in conjunction with an ET-11A or ET-12A (please order separately), allows easy switching of up to 99 LAVA® Design infrared heaters. The frequency range of 868 MHz ensures a long range and optimal connection. Can be easily used with all LAVA® 2.0, through the Plug & Play connection system.

TECHNICAL DATA



- > Switching current: 16 A, 230 V
- > Transmission frequency: 868 MHz
- > Range: 100 - 300 m
- > Dimensions: 140 x 54 x 25 mm
- > Protection rating: IP 20
- > Heating/cooling switch
- > Connection: special plug, 50 cm
- > Approval: CE compliant

Control and thermostat for LAVA® GENERATION 2.0

RG: 007 | DT: ex stock

Type	Order no.	Description
LAVA-F	39714	Radio receiver with plug for all LAVA 2.0, 16 A
ET-11A	35891	Electronic radio-controlled room thermostat
ET-12A	35890	Electronic radio-controlled room thermostat with timer

LAVA®-R - The integrated thermostat



USE

The LAVA®-R thermostat can be easily fitted to all LAVA® 2.0 units using the connection system. In combination with the eNEXHO home automation system, you can conveniently control your LAVA® Design infrared heating using a smartphone, tablet or PC, including when you are out and about.

TECHNICAL DATA



- > Voltage: 230 V
- > Switching current: 16 A
- > Temperature range: 0 - 35 °C
- > Dimensions: 251 x 31 x 62 mm
- > Protection rating: IP 24
- > Connection: special plug, 50 cm
- > Approval: CE compliant

Control and thermostat for LAVA® GENERATION 2.0

RG: 007 | DT: ex stock

Type	Order no.	Description
LAVA-R	39713	Thermostat with plug, for all LAVA 2.0, 5 - 35 °C, 16 A, step switch 60/95 °C, eNEXHO ready